



CRUSHER TRACK GCR 98



CRUSHER TRACK GCR98

TECHNICAL SPECIFICATIONS

Jaw crusher	type	R98
Inlet dimensions	mm	900x800
CSS range	mm	30÷120
Feeding hopper		
Standard capacity	m ³	6
Feed height	m	4.2
Feeder	type	EV 90/2.4
Width	mm	950
Length	mm	2400
Vibrating scalper	type	VP 150/9.SR
Width	mm	1000
Length	mm	1500
Decks	n.	2
Reversible conveyor		
Width	mm	750
Length	mm	1700
Main conveyor		
Width	mm	800
Length	mm	10400
Engine	type	FPT N67TE3F
Power	kW	195
Tracks	type	D4

Performance*

Max feed size	mm	700-750
Production	ton/h	70÷240
Transport dimensions		
Length	mm	12580
Width	mm	2550
Height	mm	3300
Weight (excluding options)	kg	36100
Standard equipment:		
Remote control for feeder		
Remote control for tracks		
Options:		
- Side conveyor		
- Overband magnet		
- Dust suppression system		
- Lubricating unit		
- Process monitoring interlocking sensors		
- Hopper extensions		
- Belt protection crusher discharge plate		
- Impact bars in main conveyor charge area		
* Depending on the type and consistency of the feed material, on the pre-screen selected and on the end product required.		

Flexible and user-friendly mobile tracked unit for major demolition works, recovery of in-pit materials and quarrying applications. Equipped with a highly sturdy jaw crusher and a 1580 mm deep crushing chamber.

Automatic hydraulic jaw adjustment system. It features a turbo diesel engine and variable-displacement pumps (load sensing system) to optimize power and fuel consumption.



The specifications shown in this brochure are not binding. REV reserves the right to make any change without notice.

REV. 01 02/07/2012



REV S.r.l.
Via Marechiese, 66
47864 Pennabilli (RN) - Italy
Tel +39 0541 928474 - Fax +39 0541 928157
<http://www.rev.it> • e-mail: rev.srl@rev.it

