



# CRUSHER TRACK GCS 109



TECHNICAL SPECIFICATIONS	
<b>Jaw crusher</b>	<b>type R109</b>
Inlet dimensions	mm 1070x900
CSS range	mm 60÷200
<b>Feeding hopper</b>	
Standard capacity	m <sup>3</sup> 9
Feed height	m 4.3
<b>Feeder</b>	<b>type RAL 1050/3.9</b>
Width	mm 1050
Length	mm 3900
<b>Vibrating scalper</b>	<b>type VP 150/10.SR</b>
Width	mm 1050
Length	mm 1500
Decks	n. 2
<b>Reversible conveyor</b>	
Width	mm 1000
Length	mm 2000
<b>Main conveyor</b>	
Width	mm 1150
Length	mm 10900
<b>Engine</b>	<b>type CAT® C9</b>
Power	kW 224
<b>Tracks</b>	<b>type D6</b>

Performance*	
Max feed size	mm 700-800
Production	ton/h 120÷400
<b>Transport dimensions</b>	
Length	mm 14700
Width	mm 2820
Height	mm 3600
<b>Weight (excluding options)</b>	<b>kg 53200</b>
<b>Standard equipment:</b>	
Remote control for feeder	
Remote control for tracks	
<b>Options:</b>	
- Side conveyor	
- Overband magnet	
- Dust suppression system	
- Lubricating unit	
- Process monitoring interlocking sensors	
- Belt protection crusher discharge plate	
- Impact bars in main conveyor charge area	
- Demolition arm	
* Depending on the type and consistency of the feed material, on the pre-screen selected and on the end product required.	

Mobile crushing unit equipped with a sturdy high-capacity crusher, suitable for large quarries or big demolitions works. Apron feeder and pre-screen for very-difficult-to-process materials. Last-generation electronic Diesel engine that drives a hydraulic system supplied with

variable-displacement pumps (load-sensing system) to optimize power and fuel consumption. Advanced safety system, respect of the environment and easy maintenance.



The specifications shown in this brochure are not binding. REV reserves the right to make any change without notice.

REV.03 03/07/2012



REV S.r.l.  
Via Marechiese, 66  
47864 Pennabilli (RN) - Italy  
Tel +39 0541 928474 - Fax +39 0541 928157  
<http://www.rev.it> • e-mail: [rev.srl@rev.it](mailto:rev.srl@rev.it)

