



CRUSHER TRACK GCV 100



TECHNICAL SPECIFICATIONS	
Jaw crusher	tipo R100
Inlet dimensions	mm 1015x650
CSS range	mm 30÷120
Feeding hopper	
Standard capacity	m ³ 6
Feed height	m 3.9
Feeder	tipo EV 90/2.7
Width	mm 900
Length	mm 2700
Main conveyor	
Width	mm 800
Length	mm 8770
Engine	tipo CAT® C6.6
Power	kW 151
Performance*	
Max feed size	mm 500-600
Production	ton/h 60÷180
Tracks	tipo FL6

Transport dimensions	
Length	mm 12230
Width	mm 2550
Height	mm 3100
Weight (excluding options)	kg 29030
Standard equipment:	
Remote control for feeder	
Remote control for tracks	
Options:	
- Side conveyor	
- Overband magnet	
- Dust suppression system	
- Lubricating unit	
- Process monitoring interlocking sensors	
- Hopper extensions	
- Belt protection crusher discharge plate	
- Impact bars in main conveyor charge area	
* Depending on the type and consistency of the feed material, on the pre-screen selected and on the end product required.	

Compact and user-friendly mobile jaw crusher equipped with automatic hydraulic adjustment system for jaws opening. Specifically designed for small and medium working sites, where a large

feed opening, excellent production and fast and easy maintenance are required. It features a turbo Diesel engine and a hydraulic control unit with load sensing pump to optimize power and fuel consumption.



The specifications shown in this brochure are not binding. REV reserves the right to make any change without notice.

REV.05 03/07/2012



REV S.r.l.
Via Marechiese, 66
47864 Pennabilli (RN) - Italy
Tel +39 0541 928474 - Fax +39 0541 928157
<http://www.rev.it> • e-mail: rev.srl@rev.it

