



SCREENING TRACK GS 45/SP



SCREENING TRACK GS 45/SP

TECHNICAL SPECIFICATIONS			
Vibrating screen	type	VN 450/SR	
Deck dimensions	mm	1500x4500	
Number of decks	n.	2	
Apron feeder	type	RAL 950/3.5L	
Width	mm	9500	
Length	mm	3500	
Under-screen stockpiling conveyor			
Width	mm	650	
Length	mm	7900	
Fines conveyor			
Width	mm	1200	
Length	mm	5200	
Mid-size stockpiling conveyor	type	Chevron	
Width	mm	650	
Length	mm	7500	
Overflow stockpiling conveyor	type	Chevron	
Width	mm	1200	
Length	mm	4700	
Engine	type	CAT® C4.4 ACERT	
Power	kW	94	

Performance*			
Max feed size	mm	600/700	
Production	ton/h	100÷350	
Tracks	type	FL6	
Transport dimensions			
Length	mm	14000	
Width	mm	2550	
Height	mm	3300	
Weight (excluding options)	kg	25200	
Standard equipment:			
- Remote control for tracks			
- Remote control for feeder			
- Top bar deck			
- Bottom net deck			
Options:			
- Automatic lubricating unit			
- Dust suppression system			
- Bottom deck: fingers - Arpa mesh screens			
* Depending on the type and consistency of the feed material and the end product required.			

Mobile screening unit able to process large-size materials, with high-level performance and low operating costs. Regular transport dimensions onto standard platform; extremely fast starting and putting in working position by unfolding its conveyors and hydraulically positioning hopper and feeder.

First-rate engine and hydraulic components. The screen can be featured with different types of screening decks. It can be easily reached for maintenance or net replacement thanks to the hydraulic lifting system. Flexible and perfectly suitable for reclamation jobsites, quarrying and recycling applications.



The specifications shown in this brochure are not binding. REV reserves the right to make any change without notice.

REV.01 09/07/2012



REV S.r.l.
Via Marechiese, 66
47864 Pennabilli (RN) - Italy
Tel +39 0541 928474 - Fax +39 0541 928157
<http://www.rev.it> • e-mail: rev.srl@rev.it

