



# CRUSHER TRACK GCC 3800



TECHNICAL SPECIFICATIONS		
<b>Cone crusher</b>	<b>type</b>	CH 430 (H3800)
Concave diameter	mm	1060
Regolazione CSS <sup>(1)</sup>	mm	6÷38
<b>Feed hopper</b>		
Standard capacity	m <sup>3</sup>	3
Feed height	m	3.6
<b>Feed conveyor</b>		
Width	mm	750
Length	mm	4100
<b>Main conveyor</b>		
Width	mm	800
Length	mm	9650
<b>Engine</b>	<b>type</b>	CAT® C7
Power	kW	186
<b>Tracks</b>	<b>type</b>	D4

Performance <sup>(2)</sup>		
Max feed size <sup>(1)</sup>	mm	40÷180
Production	ton/h	60÷200
<b>Transport dimensions</b>		
Length	mm	12110
Width	mm	2550
Height	mm	3300
<b>Weight (excluding options)</b>	<b>kg</b>	<b>28400</b>
<b>Standard equipment:</b>		
Remote control for feeder		
Remote control for tracks		
<b>Options:</b>		
- Feed hopper extensions		
- Dust suppression system		
- Lubricating unit		
- Impact bars in main conveyor charge area		

<sup>(1)</sup> Depending on the type of concave and mantle installed.

<sup>(2)</sup> Depending on the type and consistency of the feed material, on the pre-screen selected and on the end product required.

With its HYDROCONE technology, this machine is a natural addition to the range of mining and quarrying equipment based on REV's forty years of experience handling aggregates.

The cone crushers feature automatic adjustment for secondary and tertiary crushing, an outstanding performance, very low wear, easy maintenance and excellent product cubicity.

The extraordinary versatility of the LOAD SENSING hydraulic system and the available range of cavities make the GCC 3800 extremely flexible and

ideal for numerous site applications, when combined with primary and screening track-mounted machines.

The cones in the GCC series have automatic adjustment and safety systems in case of overloads or non-crushable parts, so that material can pass through and the shaft is automatically returned to its starting position.

The separate lubrication system with independent pump ensures complete lubrication even before start-up.



The specification shown in this brochure are not binding. REV reserves the right to make any change without notice.

REV.01 07/12/2012



REV S.r.l.  
Via Marechiese, 66  
47864 Pennabilli (RN) - Italy  
Tel +39 0541 928474 - Fax +39 0541 928157  
<http://www.rev.it> • e-mail: [rev.srl@rev.it](mailto:rev.srl@rev.it)

