



**CRUSHING & SCREENING  
TRACK  
GCMV 120/50P**



# CRUSHING & SCREENING TRACK GCMV 120/50P

TECHNICAL SPECIFICATIONS		
<b>Impact crusher</b>	type	ML 12.5
Inlet dimensions	mm	1200x610
CSS adjustment		hydraulic
<b>Vibrating screen</b>		VNO 518/B
Deck dimensions	mm	5000x1800
Number of decks	n.	3
<b>Feed hopper with tipping grid</b>		
Capacity	m <sup>3</sup>	3
<b>Reciprocating feeder</b>	type	RA 70/L
Extracting plate width	mm	700
<b>Main feed conveyor</b>		
Width	mm	700
Length	mm	16500
<b>Crushed conveyor</b>		
Width	mm	700
Length	mm	8000
<b>Swivelling stockpiling belt</b>		
Width	mm	800
Length	mm	7000
<b>N. 2 side stockpiling conveyors</b>		
Width	mm	500
Length	mm	9000
<b>Fines conveyor</b>		
Width	mm	800
Length	mm	5000

<b>Transverse re-circulating conveyor</b>		
Width	mm	500
Length	mm	1500
<b>Engine</b>	type	CAT® C9
Power	kW	261
<b>Tracks</b>		D5
<b>Performance*</b>		
Max feed size	mm	100÷250
Production	ton/h	100÷280
<b>Transport dimensions</b>		
Length	mm	18700
Width	mm	3000
Height	mm	4350
<b>Weight (excluding options)</b>	kg	42600
<b>Standard equipment:</b>		
Remote control for feeder		
Remote control for tracks		
<b>Options:</b>		
- Dust suppression system		
- Lubricating unit		
- Water tank		
- Vibrating grid above feed hopper		
* Depending on the type and consistency of the feed material, on the pre-screen selected and on the end product required.		

A compact crushing solution for both recycling and final screening all in one. Diesel motor driven components with hydraulic adjustment.



The specifications shown in this brochure are not binding. REV reserves the right to make any change without notice.

REV. 00 05/12/2012



REV S.r.l.  
Via Marechiese, 66  
47864 Pennabilli (RN) - Italy  
Tel +39 0541 928474 - Fax +39 0541 928157  
<http://www.rev.it> • e-mail: [rev.srl@rev.it](mailto:rev.srl@rev.it)

